

TURNTABLE

TECHNICAL SHEET

CAR **DOK** 

DOUBLE YOUR PARKING SPACE

CARDOK Turntable

Simplifies parking in narrow areas, indoor and outdoor.
Secure, Fast and Bespoke.

Installation for private houses, buildings, hotels, offices...

CAR  .COM

SWISS ENGINEERING

CARDOK SA

Rue de Riant Coteau 11
1196 Gland • Switzerland

phone: +41 22 776 60 51
info@cardok.com

Any reproduction or copying is prohibited without our
written permission. Subject to change. Ver. 04-2020

MODELS AND CHARACTERISTICS

CARDOK TURNTABLE STANDARD

Platform load max. 3000kg, 5m. in diameter.

CARDOK TURNTABLE EXCLUSIVE

Design on mesure following your request.

	Standard	Options
Platform load	3000kg	3500kg / other
Dimensions available	5000mm	4500 / 5500 / 6000 / other
Pit depth	450mm	150 / other
Speed	1RPM	

Electricity: 230VAC / 1Ph

Power of engine: 1.5kW

Command: control panel and remote controls

Installation: indoor or outdoor

Platform finish: 40mm deep tray ready to receive a waterproof layer (if applicable) and revetment of your choice: asphalt, gravel, tiles etc.

Standard load: 75kg/m². As option: ribbed aluminium plates, galvanized steel plates, ribbed aluminium anodic oxidized in black

Speed: 1 RPM

Noise: very little noise

Security: operated by «hold to operate» remote control

Temperature: -25°C and +50°C

Ecology: component materials almost entirely recyclable